3000 mm x 1500 mm CNC Fiber Laser $_$ available to test and purchase

G-WEIKE®	G Weike Fiber Laser LF3015GA II - 3KW Profile Cutter _ Exchange Table Pricing Outline _ EX STOCK SPECIAL				INDEPTH TECHNOLOGY UTD	
Model	Main Points		Power	Installed NZD	Machine Pictures	
LF3015GA II Sheet only machine with exchange table	* Max working area: 3000 x 1500 mm * Aviation aluminum beam * Exchange platform * Protect Cover * Swiss RAYTOOLS auto focus laser head * Japan YASKAWA servo motor on X/Y/Z axis * Reducer:France Motoreducer * France SCHNEIDER electron components * Rack: Taiwan YYC * Taiwan PMI/HIWIN Guide rail * Pneumatic parts:Taiwan AirTAC/ SMC * Automatic rail lubrication system * CYPCUT & CYPNEST system * S & A Water cooling system * Camera for inside working watch * Light curtain for echange table * Voltage stabilizer * Safety switch * Auto exhaust- along with centrifugal fans			\$139,900		
DBZY20A Air Compressor		16 Bar maximum pressure. 15KW motor, 500L tank			DOTOR	
Total excluding GST \$139,900					Incl GST \$160,885	
Technical Parameters for LF3015GA						
Model Laser power			LF3015GA II 3 kW GW La			
Total Weight			6,600kg			
Dimension			8850*2850*2310 mm			
X-axis stroke			1500mm			
Y-axis stroke			3000mm			
Z-axis stroke			290mm			
	X/Y axis position accuracy			±0.03		
X/Y axis reposition accuracy			±0.02			
Max. Moving speed			80m/min			
Maximum acceleration Max. Working capacity of sheet table			1.5g 700kg			
Max.	Motor Power			X: 0.85KW Y:1.8KW Z:750W		
Transmission			Double driver rack and gear			
Haroniloolul			Double univerrack and gear			

Installed, training provided, and operation supported

